

*Strength on all fronts™*

# DS Warranty

## November 2022

---



**DS Stålprofil**  
Quality. Strength. Since 1969.

# Warranty terms and conditions

---

- The product must not be used in particularly corrosive or aggressive environments, e.g. in air with a high salt content, be in constant contact with water or in contact with e.g. chemicals, smoke, copper, lead, manure, dust, ash and other external corrosion-causing elements.
- The product must not come into contact with wet concrete, wet timber and pressure-impregnated wood.
- The product must be installed in accordance with DS Stålprofil's installation instructions.
- The product must be installed using DS Fittings and DS Sealing Accessories.
- The product must be maintained and inspected in accordance with the applicable guidelines issued by DS Stålprofil A/S.
- The product is installed at the correct roof pitch.
- The product is not exposed to mechanical effects after it has left the factory.
- Products in a rain shadow must be washed in the correct way.
- The product must be stored correctly before it is installed and installed not more than one month after the invoice date.
- The current owner must be able to submit written documentation that describes the order and/or the invoice number or other proof of purchase.
- A complaint must be submitted to DS Stålprofil A/S no later than three weeks from when the damage was discovered or from when it should have been discovered.
- DS Stålprofil A/S must have the opportunity to inspect the product while it is installed.

# Compensation terms and conditions

---

- When an entitled claim is received in accordance with the warranty terms and conditions, and depending on the evaluation of the product, DS Stålprofil A/S will choose to either recoat the product or supply new products as a replacement for the defective products.
- Liability related to this warranty is limited to the original invoice value and does not cover the costs of removal or re-installation.
- DS Stålprofil A/S is not liable for direct or indirect losses, including production losses, rent losses, consequential damages and damages to the other parts of the building structure or buildings.
- The warranty for the replacement or re-coating of products applies during the remaining period of the original warranty.
- The warranty does not apply to colour differences when products are replaced.
- The warranty does not cover any corrosion formation at sheet edges and around perforations of products.
- The warranty does not apply to the coating on the rear of the products.

**Please note that tension-induced bulging in thin plate steel is not covered by the warranty.**



Denmark's best warranty terms and conditions.

At DS Stålsprofil, you get a full 30-year warranty. This means that the coverage is the same from the first to the last day of the warranty period – even for holiday homes located on the coast.



# Warranty steel sheets

---

This warranty is issued by DS Stålprofil A/S. The warranty covers in-house manufactured steel sheets, which during the warranty period have developed corrosion holes as a consequence of defects in manufacture or materials.

The warranty applies from the date of purchase and covers the following products:

- DS Trapezoidal 20-115
- DS Trapezoidal 35-206
- DS Trapezoidal 35-190
- DS Trapezoidal 45-333 S
- DS Sinusoidal 18-75
- DS Sinusoidal 35-143
- DS Rib Sheet 22-270
- DS Inverted Rib Sheet 22-270
- DS Unique 400
- DS Distinct 350
- DS Distinct 460
- DS Distinct 1050
- DS Distinct 1070
- DS Premium Facade Panel
- DS Nordic Click Seam

**50 µm GreenCoat Pural BT:** 30-year warranty

**50 µm GreenCoat Pural BT Matt:** 30-year warranty

**36 µm GreenCoat Pro BT Matt:** 30-year warranty

**36 µm Pladur Ice Crystal:** 25-year warranty

**25 µm Polyester:** 20-year warranty

**Aluzink AZ 185+:** 20-year warranty

If used in an area within 10 km of the coastline, the warranty period is halved. However, if Aluzinc is used in an area within 10 km of the coastline, it is not covered by the warranty.

Please note that the warranty does not cover products that are perforated. It is recommended that stainless fittings are used with installations in an area within 10 km of the coastline.

When installing solar panel systems on roof sheets, the unchanged perforation warranty applies to GreenCoat® Pural BT, GreenCoat® Pural BT Mat, and GreenCoat® Pro BT Mat. No warranty is provided when choosing other surface types.

This warranty applies to all deliveries made from January 2020.

# Warranty light sheets

---

This warranty is issued by DS Stålprofil A/S. The warranty covers PVC and PC light sheets, which during the warranty period must have a light transmission of less than 70%.

The warranty applies from the date of purchase and covers the following products:

- DS Trapezoidal 20-115
- DS Trapezoidal 35-206
- DS Trapezoidal 35-190
- DS Trapezoidal 45-333 S
- DS Sinusoidal 18-75
- DS Sinusoidal 35-143
- DS Rib Sheet 22-270
- DS Unique 400
- DS Distinct 1050
- DS Distinct 1070



**PVC Light sheets:** 5-year warranty  
**PC Light sheets:** 10-year warranty

This warranty applies to all deliveries made from January 2020.

# Warranty gutter range

---

This warranty is issued by DS Stålprofil A/S. The warranty covers gutters, downpipes and fittings, which during the warranty period have developed corrosion holes as a consequence of defects in manufacture or materials.

The warranty applies from the date of purchase and covers the following products:

- DS Gutters
- Downpipes
- DS fittings for gutter range



**50 µm Nova:** 20-year warranty  
**Aluzink:** 15-year warranty

This warranty applies to all deliveries made from January 2020.

# Maintenance

---

To ensure the optimal use of steel sheet cladding, it is important that the maintenance stated below is followed. The following points must be checked by inspection:

- |   |  |   |  |
|---|--|---|--|
| 1 | There is no dirt accumulations and all of the cladding is clean.       | 4 | Flashing is secure, edges sealed with the surrounding materials. |
| 2 | The cladding is intact. Particular attention is paid to cutting edges. | 5 | Rib strip is correctly in place for optimal sealing.             |
| 3 | Screws and other fittings have not become loose                        | 6 | Any damage that has occurred is immediately repaired.            |

# Cleaning

---

It is important that the cladding is cleaned at suitable intervals, however at least once a year. Note that some exterior surfaces may be located in a rain shadow, e.g. facade cladding underneath an overhang. These surfaces must be cleaned more often otherwise greater soiling can build up because there has not been any natural rinsing from rain.

Dirt deposits and similar may be washed off using a soft brush and mild soapy water.

# DS Stålsprofil takes care of the environment

---

DS Stålsprofil does not use or manufacture products that pollute or adversely affect the environment where they shall be used. All of the products and structural elements can be disposed of, destroyed or recycled in a way that is completely safe for the environment.

DS Stålsprofil does not use chemicals that are hazardous to health if the work can be carried out in a sensible way without the use of such chemicals.



Find inspiration on  
[www.ds-staalprofil.com](http://www.ds-staalprofil.com)

Steel is perfect for roofs and facades. Above all, because steel is strong.

This means you get a unique solution that has a long lifetime, which protects your building optimally – and requires a minimum of maintenance. At the same time, roof and facade solutions from DS Stålsprofil provide you with the freedom to precisely create the look you want.

*Strength on all fronts™*



**DS Stålsprofil**

---

DS Stålsprofil A/S  
Andrupvej 9 · DK-9500 Hobro  
Tel.: +45 96 57 28 28  
[www.ds-staalprofil.com](http://www.ds-staalprofil.com)

DEALER: